

CLEAN POWER

HP 350



CLEANING AND EMERGENCY RECOVERY - ONE SOLUTION FOR ALL

SCHWING CLEAN POWER 350

This machine solves your problems with pipeline blockages and at the same time can be used as an auxiliary emergency power pack.

Technical Data

Engine	Petrol engine 2 cylinder, 4-stroke Maximum torque at 3600 rpm 17,7 (24) kW/HP Fuel tank 15, petrol, unleaded
Water connection or hydr. oil connection	Max. feed temperature 60 Min. feed volume 1500 Max. feed pressure 10 bar Inlet hose diameter (min.) 1 Zoll
Performance data	Working pressure 5...35 Pa (bar) (50...350) Flow rate 500...1260 l/h
Noise emission	Sound pressure level (EN 60704-1) 91 dB(A)
Dimensions and weights	1025 x 780 x 1100 L x W x H mm Weight without accessories 128
Standard equipment	rotary jet brass nozzle, 1,5 m lance, 10 m HP hose, accessories for use as hydraulic power pack

Options

Lance 0.75 m, flat jet nozzle point jet nozzle repair kit rotary nozzle filter and water filter set, repair kit pump, repair kit over flow valve, fitting for hose extension, HP hose 20m, Set of O-rings for hose between lance and nozzle. spark plug, gasoline oil / air filters for engine, spare tyre.

For further questions, please contact us



SCHWING STETTER (INDIA) PVT LTD

ISO 9001:2008 :: OHSAS 18001: 2007 :: ISO 14001:2004

F 71 - 72, SIPCOT Industrial Park, Irungattukottai, Sriperumpudur Taluk, Kancheepuram District, Tamil Nadu - 602105.
Tel : 044 2715 6780 / 781, 47108100 Fax : 044 2715 6539 Email : schwing@vsnl.com, chennai@schwingstetterindia.com

MUMBAI | NEW DELHI | HYDERABAD | BANGALORE | KOLKATA | AHMEDABAD | PUNE | VIZAG | MANGALORE
COCHIN | MOHALI | BHUBANESWAR | GUWAHATI | RAIPUR | JAMSHEDPUR | COIMBATORE | SURAT | PATNA